

Duckhams Fleetmaster 20W-40 CF-4**PRODUCT DESCRIPTION**

Duckhams Fleetmaster 20W-40 CF-4 is a multi-grade diesel engine oil for heavy-duty diesel engines. Formulated using existing additive technology and high-quality virgin base oils to meet current specifications and provide complete protection for all new and old generation vehicles.

Duckhams Fleetmaster 20W-40 CF-4 is a mineral engine oil designed to lubricate and protect high-speed diesel engines. Gives excellent protection against soot, and corrosion and reduces piston deposits and oil consumption.

FEATURES AND BENEFITS

- Excellent soot control, reduces oil thickening and maintains engine performance, and protects against abrasive wear within the engine.
- Excellent protection against rust and corrosion, maintaining the condition and prolonging the life of the engine.
- Protects engine from wear which extends engine operating life and maintains engine performance, reducing total running costs.
- Reduces piston deposits and maintains engine cleanliness ensuring the engine running in optimum condition.
- Reduces oil consumption, minimising top-up requirements and reducing operating costs.

SPECIFICATIONS AND APPROVALS

Meets or exceeds the required performance level for:

API CF-4

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity Grade	-	20W-40
Viscosity @ 100 °C	cSt	14.08
Viscosity @ 40 °C	cSt	111.99
Viscosity Index	-	126
CCS @ -20 °C	cP	4,297
Flash Point (Closed Cup)	°C	218
Pour Point	°C	-24
Total Base Number	mgKOH/g	7.5
Density @ 15 °C	Kg/L	0.8700

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.