



DUCKHAMS Q 20W-50 SL/CF

PRODUCT DESCRIPTION

Duckhams Q was the first multigrade engine oil marketed in Europe. Duckhams Q 20W-50 SL/CF is a mineral-based engine lubricant formulated using updated additive technology and high-quality virgin base oils to meet older specifications and provide reliable protection for modern passenger cars.

Duckhams Q 20W-50 SL/CF is multi-grade engine oil, suitable for year-round use, formulated to provide reliable anti-wear and corrosion protection. Deposit control maintains engine cleanliness, and low volatility formulation reduces oil consumption ensuring the correct level of protection throughout the oil drain interval.

FEATURES AND BENEFITS

- Good anti-wear properties protect the engine.
- Good Rust and Corrosion protection.
- Deposit control maintains engine cleanliness.
- Multi-grade engine oil, suitable for year-round use.
- Low Volatility reduces oil consumption.
- Original, distinctive, Duckhams green colour.

SPECIFICATIONS AND APPROVALS

Can be used where the following specification is required:

API SL/CF

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity Grade	-	20W-50
Colour	-	Green
Viscosity @ 100 °C	cSt	18.87
Viscosity @ 40 °C	cSt	161.3
Viscosity Index	-	132
CCS @ -15 °C	cP	5,474
Flash Point (Closed Cup)	°C	220
Pour Point	°C	-27
Total Base Number	mgKOH/g	5.4
Density @ 15 °C	Kg/L	0.8742

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.
