



DUCKHAMS QS 5W-30 SL/CF A5/B5

PRODUCT DESCRIPTION

Duckhams QS 5W-30 SL/CF A5/B5 is a low viscosity, full SAPS fully synthetic engine oil for use in gasoline and diesel vehicles. Formulated using modern additive technology and high-quality synthetic base oils to meet the requirements of current vehicles and provide advanced protection for modern passenger cars.

Duckhams QS 5W-30 SL/CF A5/B5 improves engine and fuel efficiency and reduces emissions whilst still ensuring high-temperature protection. It gives excellent engine cleanliness reducing sludge and deposit formation. It provides easy cold start and ideal lubrication at elevated temperature and ensures low oil consumption and cold start protection against wear.

FEATURES AND BENEFITS

- Reduces internal friction within the engine, increasing engine efficiency, and reducing fuel consumption extending engine life and reducing running costs.
- Provides exceptional anti-wear and corrosion protection extending component and engine life.
- Stay in grade formulation designed to maintain the viscosity of the oil, ensuring suitable protection for engines throughout extended oil drain intervals, irrespective of driving style.
- Excellent low-temperature properties ensure rapid lubrication throughout the engine giving improved cold starting and minimising engine wear at startup.
- Thermally stable formulation reduces sludge and deposit formation keeping the engine clean to ensure the engine runs at its full potential from oil change to oil change.
- Low volatility synthetic base oil reduces oil consumption and oil thickening and gives lower hydrocarbon emissions.

SPECIFICATIONS AND APPROVALS

Meets or exceeds the required performance level for:

ACEA A5/B5, API SL/CF, Ford WSS-M2C913-D, Ford WSS-M2C913-C, JLR STJLR.03.5003

Suitable for use where the following specifications are recommended:

Ford WSS-M2C913-B, Ford WSS-M2C913-A

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity Grade	-	5W-30
Viscosity @ 100 °C	cSt	9.99
Viscosity @ 40 °C	cSt	54.87
Viscosity Index	-	171
CCS @ -30 °C	cP	4,122
Flash Point (Closed Cup)	°C	204
Pour Point	°C	-42
Total Base Number	mgKOH/g	9.9
Density @ 15 °C	Kg/L	0.8533

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.