

DUCKHAMS QT Supreme Scooter 10W-40 SL/MB

PRODUCT DESCRIPTION

Duckhams QT Supreme Scooter 10W-40 SL/MB is a semi-synthetic multi-grade engine oil, designed for performance, using modern additive technology and high-quality base oils to meet the requirements of modern four-stroke scooter engines.

Duckhams QT Supreme Scooter 10W-40 SL/MB has been carefully formulated to meet the low friction requirements of modern Scooter engines, reducing wear and corrosion, extending engine life, whilst reducing sludge and deposit build-up, maintaining engine cleanliness, and engine performance throughout the oil drain interval.



FEATURES AND BENEFITS

- Low Friction engine oil for use in Scooters with separate automatic transmission systems. Also suitable for Motorcycles not fitted with a wet clutch or combined engine, clutch and gearbox and requiring an oil of this viscosity and specification.
- Formulated using high-quality synthetic base oils with hydro processed mineral oils to give improved oxidation and thermal stability, even at high operating temperatures, prolonging the life of the oil, ensuring the engine is suitably lubricated, giving sustained engine performance.
- Lubricant designed to ensure anti-wear and corrosion protection, irrespective of riding style, throughout the oil drain interval, reducing component wear and extending component and engine life.
- Carefully balanced detergent and dispersant additives reduce sludge and deposit build-up, providing excellent engine cleanliness, and maintaining optimum engine performance, power and efficiency from oil change to oil change.

APPLICATIONS

Suitable for use in a wide range air-, and liquid-cooled four-stroke Scooters fitted with separate automatic, or CVT, transmissions. Also suitable for use in motorcycles not fitted with wet clutch or combined engine, clutch and gearbox lubricant system

Not suitable for use in engines fitted with wet clutches, or combined engine, clutch and gearboxes, which require JASO MA, JASO MA1 or JASO MA2 Lubricants.

Always refer to your owner's handbook when selecting oil for your vehicle.



SPECIFICATIONS AND APPROVALS

Meets or exceeds the required performance level for:

API SL, JASO MB

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity Grade	-	10W-40
Viscosity @ 100 °C	cSt	13.86
Viscosity @ 40 °C	cSt	96.40
Viscosity Index	-	145
CCS @ -25 °C	cP	6,288
Pour Point	°C	-39
Total Base Number	mgKOHg ⁻¹	6.2
Density @ 15 °C	Kg/L	0.8682

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.