

Duckhams D-Clutch

HIGH QUALITY DCT FLUID FOR MODERN CARS

PRODUCT DESCRIPTION

Duckhams D-Clutch is a specially formulated, fully synthetic Dual Clutch Transmission fluid suitable for a wide range of vehicles fitted with DSG or DCT wet clutch transmissions, including: Volkswagen, Audi, BMW, Seat, Skoda, Ford, Renault, Peugeot, Mitsubishi, Chrysler, Porsche, Jaguar & Volvo

SPECIFICATIONS

Recommended for certain DSG and DCT Volkswagen, Audi, BMW, Seat, Skoda, Ford, Renault, Peugeot, Mitsubishi, Chrysler, Porsche, Jaguar & Volvo transmissions.

BMW Drivelogic 7-speed (Getrag) DCTF-1; BMW 6-Speed DCT; BMW MTF LT-5; Borg Warner; Bugatti Veyron; Castrol BOT 341; BOT 450; Transmax Dual; Chrysler 68044345 EA & GA; Powershift 6-speed Getrag; DCT-1; Ferrari 7-speed (Getrag)/TE DCT-3; Ford/Nissan Powershift 6-speed (GFT) / Ford WSS-M2C936A; Part # 1490763/1490761; WSS-M2C200-D2 / XT-11-QDC; Mitsubishi TC-SST 6-speed (GFT) / MZ320065 Dia Queen SSTF-1; Pentosin FFL 2; Pentosin FFL 3; Pentosin FFL 4; Peugeot/Citroen DCS 6-speed (GFT)/9734.S2; Renault EDC 6-speed (Getrag); Shell TF DCT-F3; Volvo Powershift 6-speed (GFT) / 1161838/1161839; VW (Audi, Seat, Skoda) 6-speed; VW/Audi TL 52529 (spec) / G 052 529 A2 or A6 (fluid); VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid); ZF/ Porsche Oil #999.917.080.00; MB 236.21; VW G 055 529

FEATURES AND BENEFITS

- Fully synthetic high performance DCT fluid.
- Suitable for use in wide range of vehicles fitted with DSG or DCT wet clutch transmissions.
- Provides excellent friction durability, scuffing protection and fatigue resistance.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	7.5 cSt
Viscosity @ 40°C	37 cSt
Phosphorus	0.02%
Colour	Brown
Pour Point	-36°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.