

Duckhams QXR 0W-30 VW

FULLY SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

PRODUCT DESCRIPTION

Duckhams QXR 0W-30 VW is a fully synthetic engine oil exceeding 5W-30 VW 504/507 fuel efficiency requirements by over 25%. Designed to contain mid SAPS for enhanced CAT and DPF protection.

SPECIFICATIONS

Recommended for vehicles requiring 0W-30 oils meeting the following specifications: ACEA C3; VW 504 00, VW 507 00; Porsche C30

FEATURES AND BENEFITS

- Fully synthetic high performance engine oil.
- Exceeds 5W-30 VW 504/507 fuel efficiency requirements by over 25%.
- Suitable for petrol and diesel engines.
- Designed to contain mid SAPS for enhanced CAT and DPF protection.

APPLICATIONS

AUDI, HYUNDAI, LAMBORGHINI, PORSCHE, SKODA, VOLKSWAGEN

May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.840 g/cm ³
Viscosity @ 100°C	11.8 cSt
Viscosity @ 40°C	59 cSt
Viscosity Index	201
Viscosity CCS @ -35°C	5900 cP
T.B.N.	8.2 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.08%
Colour	Amber
Flash Point	>200°C
Pour Point	-48°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.