

## Duckhams QS 10W-40 RMV

SEMI SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

### PRODUCT DESCRIPTION

Duckhams QS 10W-40 RMV is a semi synthetic, high performance 10W-40 oil, suitable for petrol and diesel vehicles including those with fuel injected and multivalved engines.

### SPECIFICATIONS AND APPROVALS

Recommended for vehicles requiring 10W-40 oils meeting the following specifications:

ACEA A3/B4; API SN/CF

RN0700, RN0710; PSA B71 2300; MB 229.3

Approved under VW standard 501 01 and VW standard 505 00

### FEATURES AND BENEFITS

- Semi synthetic, high performance engine oil.
- Suitable for petrol and diesel vehicles.

### APPLICATIONS

FIAT, FORD, HYUNDAI, LAND ROVER, NISSAN, OPEL/VAUXHALL, RENAULT, VOLKSWAGEN

May also be suitable for other vehicles. Always refer to your owner's handbook.

### HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

### STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

### SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



### TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.865 g/cm <sup>3</sup>
Viscosity @ 100°C	14.2 cSt
Viscosity @ 40°C	98 cSt
Viscosity Index	149
Viscosity CCS @ -25°C	6000 cP
T.B.N.	10.7mg KOH/g
Sulphated Ash Mass	1.3%
Zinc	0.13%
Calcium	0.34%
Phosphorus	0.12%
Colour	Brown
Flash Point	>230°C
Pour Point	-39°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.