

Duckhams CHF

PREMIUM QUALITY HYDRAULIC FLUID

PRODUCT DESCRIPTION

Duckhams Central Hydraulic Fluid is a special synthetic oil based hydraulic fluid for power steering, central hydraulic and suspension level control systems.

SPECIFICATIONS

Recommended for applications requiring the following specifications:

CHF11S* and CHF202*

*CHF11S and CHF202 are registered trademarks of Pentosin-Werke GmbH

FEATURES AND BENEFITS

- Premium quality synthetic based hydraulic fluid.
- Specially formulated for power steering, central hydraulic suspension level control, stability and traction control systems.

DIRECTIONS OF USE

- **IMPORTANT:** Do not mix with other grades of ATF or Power Steering Fluids.
- Always follow vehicle manufacturer's recommendations when adding hydraulic system oil.
- Keep fluid clean and store only in original container.
- Keep container clean and tightly closed to prevent water absorption.
- Do not refill container and do not use for other liquids.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.827 g/cm ³
Viscosity @ 40°C	19 cSt
Colour	Green
Viscosity @ -40°C	1050 cSt
Viscosity Index	330
Pour Point	-54°C

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle. YYYY.MM.DD

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.