

## Duckhams QXR 0W-20 FO

FULLY SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

### PRODUCT DESCRIPTION

Duckhams QXR 0W-20 FO is a fully synthetic, low viscosity engine oil specifically developed for Ford EcoBlue diesel engines where Ford WSS-M2C952-A1 is required. Provides excellent low speed pre-ignition (LSPI) protection, delivers high fuel economy performance, whilst maintaining exceptional wear protection.

### SPECIFICATIONS

Recommended for vehicles requiring 0W-20 oils meeting the following specifications: ACEA C5, C6; API SN Plus, API SP; Dexos D; Ford WSS-M2C952-A1; MB 229.71; OV0401547; STJLR.03.5006

### FEATURES AND BENEFITS

- Fully synthetic low viscosity engine oil.
- Specifically developed for Ford EcoBlue diesel engines where Ford WSS-M2C952-A1 is required.
- Suitable for petrol and diesel engines.
- Provides excellent low speed pre-ignition (LSPI) protection.
- Delivers high fuel economy performance, whilst maintaining exceptional wear protection.

### APPLICATIONS

BMW, FORD, HYUNDAI, JAGUAR, LAND ROVER, KIA, MERCEDES, VAUXHALL  
May also be suitable for other vehicles. Always refer to your owner's handbook.

### HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

### STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

### SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



### TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.840 g/cm <sup>3</sup>
Viscosity @ 100°C	8.0 cSt
Viscosity @ 40°C	40.0 cSt
Viscosity Index	178
Viscosity CCS @ -35°C	5000 cP
T.B.N.	9.5 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.12%
Phosphorus	0.08%
Colour	Brown
Flash Point	>230°C
Pour Point	-42°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.