

PRODUCT DESCRIPTION

QXR 0W-20 MBJ

QXR 0W-20 MBJ is an ultra-low viscosity fully synthetic engine oil developed for next-generation fuel-efficient engines. It delivers reliable performance in extreme cold and maintains stability under high thermal stress. Ideal for vehicles equipped with emission control systems, this oil enhances engine cleanliness and supports extended oil change intervals.



FEATURES AND BENEFITS

- Fully synthetic formula designed for maximum fuel efficiency and engine responsiveness
- Provides smooth and reliable cold starts even at very low temperatures
- Maintains consistent protection and lubrication during both city and highway driving
- Helps reduce engine deposits and supports long-term engine cleanliness
- Suitable for vehicles with advanced emission control technologies
- Remains stable under demanding driving conditions and high temperatures

SPECIFICATIONS:

ACEA C5, ACEA C6
API SP, API SN, API SN Plus, API SN RC
ILSAC GF-5

STJLR.03.5006;
Opel/Vauxhall OV0401547;
BMW LL-17FE+ (covers BMW LL-14FE+);
MB 229.71;
Ford WSS-M2C947-B1;
Fiat 9.55535-GSX;
Chrysler MS-12145.

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity		0W-20
Density @ 20°C	Kg/m ³	0.847
KV100	cSt	8.2
KV40	cSt	41.4
VI	-	171
CCS	cP	5608
TBN		8.3
Sulphated Ash	%	0.7
Colour		Clear Amber
Flash (Closed)	°C	198
Pour Point	°C	-48

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.